



1300 35 75 85

www.nolancarpets.com.au

CONTACT US

Catherine Kent	SA/NT/WA	catherine.kent@nolans.com.au	0448 274 696
Chantal Marshall	NSW/VIC	chantal.marshall@nolans.com.au	0403 136 320
Pas Daskalakis	QLD	pas.daskalakis@nolans.com.au	0499 993 856



LUXURY VINYL TILE



STOCKED COLOURS

The high-performance Luxury Vinyl Tile collection by TOLI Select showcases sophisticated wood and stone designs, empowering designers to create striking evironments for both commercial and residential settings.



Name	Plank Dimensions
Aged Oak 2001	184.1mm x 1219.2mm



Name	Plank Dimensions
Greyish Oak 2002	184.1mm x 1219.2mm



Name	Plank Dimensions
Faded Pine 2005	184.1mm x 1219.2mm



Name	Plank Dimensions
Quebec Maple 2015	184.1mm x 1219.2mm



Name	Plank Dimensions
Cinnamon Oak 2016	184.1mm x 1219.2mm



Name	Plank Dimensions
Scandinavian Oak 2017	184.1mm x 1219.2mm



SPECIFICATIONS



Product Specifications	
Surface	UV-Reinforced PVC
Plank Dimensions	184.1mm x 1219.2mm
Sizes (mm)	304.8 × 457.2 457.2 × 457.2 457.2 × 609.6
*available on indent basis	457.2 × 914.4 152.4 × 914.4 228.6 × 1219.2
Thickness	3.0mm
Wear Layer	0.5mm
Backing	Vinyl
Finish	UV layer
Lead Time	8 weeks
Packaging Specifications	
Planks per box	15 planks per box
Coverage per box	3.37m ²
Weight per box	17.32kg
Performance Specifications	
Slip Resistance	BS 7976-2:2002 + A1:2013 Dry = 60, Wet = 32 DIN EN 16165:2023-02 Class R9
Colourfastness to Light	ISO 105-B02:2014 Method 3 ≥ 6
Abrasion Resistance	EN 660-2:1999+ A1:2003 Group T
Castor Chair	ISO 4918:2016+Amd.1:2018 No Visible Damage
Impact Sound Reduction	ISO 10140-3:2021 compliant ISO 717-2:2020 Lw = 4dB
Dimensional Stability	ISO 23999:2021 ≤ 0.09%
Static Electrical Propensity	EN 1815:2016 Method A 0.1kV
Reaction to fire	EN 13501-1:2018 Class Bfl-s1
Critical Heat Flux	EN ISO9239-1 ≥ 11kW/m ²
Smoke Rate	EN ISO 9239-1 ≤ 750%.min
Environmental Specifications	
Standards	ISO9001 and ISO14001 certified
Sustainability	Global GreenTag certified International Standard v4.0 (GreenRate Level A)
Technical Information	
Warranty *On condition tiles are glued down	Residential: 12 years Commercial: 8 years Light Industrial: 8 years
Installation	During installation, check the direction of arrows printed on the backing and keep the room temperature at 20°C or higher. The temperature change should be within 15°C. Floor tiles should be unpacked and placed at the job site 48 hours prior to the installation for adaptation to the temperature.
Maintenance	During maintenance after installation, clean the floor with detergent. After rinsing with wet mop and drying, apply resin wax. At initial maintenance, it's important to clean the floor surface thoroughly before waxing. According to traffic condition, increase the frequency of daily maintenance by mop or broom.