LUXURY VINYL TILES





AGED OAK 2001 STOCKED

| and the second second second | |
|------------------------------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

GREYISH OAK 2002 STOCKED



FADED PINE 2005 STOCKED



QUEBEC MAPLE 2015 STOCKED



CINNAMON OAK 2016 STOCKED



Installation

Maintenance

SCANDINAVIAN OAK 2017 STOCKED

| Product Specifications | |
|--|--|
| Surface | UV-Reinforced PVC |
| Plank Dimensions | 184.1mm x 1219.2mm |
| Sizes (mm) | 304.8 × 457.2 457.2 × 457.2 457.2 × 609.6 |
| *available on indent basis | 457.2 × 914.4 152.4 × 914.4 228.6 × 1219.2 |
| Thickness | 3.0mm |
| Wear Layer | 0.5mm |
| Beveling | Non-bevel |
| Backing | Vinyl |
| Finish | UV layer |
| Lead Time | 8 weeks |
| Packaging Specifications | |
| Planks per box | 15 planks per box |
| Coverage per box | 3.37 m² |
| Weight per box | 17.32kg |
| Performance Specifications | |
| Slip Resistance | BS 7976-2:2002 + A1:2013 Dry = 60, Wet = 32 DIN EN 16165:2023-02 Class R9 |
| Colourfastness to Light | ISO 105-B02:2014 Method 3 ≥6 |
| Abrasion Resistance | EN 660-2:1999+ A1:2003 Group T |
| Castor Chair | ISO 4918:2016+Amd.1:2018 No Visible Damage |
| Impact Sound Reduction | ISO 10140-3:2021 compliant |
| | ISO 717-2:2020 Lw = 4dB |
| Dimensional Stability | ISO 23999:2021 ≤ 0.09% |
| Static Electrical Propensity | EN 1815:2016 Method A 0.1kV |
| Reaction to fire | EN 13501-1:2018 Class Bfl-s1 |
| Critical Heat Flux | EN ISO9239-1 ≥ 11kW/m2 |
| Smoke Rate | EN ISO 9239-1 ≤ 750%.min |
| Environmental Specifications | |
| Standards | ISO9001 and ISO140001 certified |
| Sustainability | Global GreenTag certified |
| | International Standard v4.0 (GreenRate Level A) |
| Technical Information | |
| Warranty | Residential: 12 years |
| Warranty *On condition tiles are glued down | Commercial: 8 years |
| | Light Industrial: 8 years |
| | During installation, check the direction of arrows printed on the |

installation for adaptation to the temperature.

backing and keep the room temperature at 20°C or higher. The temperature change should be within 15°C. Floor tiles should be unpacked and placed at the job site 48 hours prior to the

During maintenance after installation, clean the floor with detergent. After rinsing with wet mop and drying, apply resin wax. At initial maintenance, it's important to clean the floor

surface thoroughly before waxing. According to traffic condition, increase the frequency of daily maintenance by mop or broom.