



# INCLINATION™



## Content

Vinyl

## Backing

Hi-Loft<sup>2</sup>™ 100% Polyester

## Finishes



## Characteristics

Antibacterial

AATCC TM 147

Mildew Resistant

Stain Resistant

No Heavy Metals

Formaldehyde Free

Easily Cleaned

Scratch Resistant

## Performance

Superior Abrasion

CFFA 1, ASTM D-4157-02  
100,000 cycles, Wyzenbeek #10 Cotton Duck

UV Stability

Xenotest: AATC TM 16-3/ CFFA-2 A1  
1,000 Hours

Cold Crack -10°F

CFFA-6A

Crocking Resistance

CFFA-7 ATCC TM 8: Pass



This fabric meets or exceeds these  
ACT performance guidelines.

\*Certification Marks owned by ACT®

## Flame Retardancy\*

Boston Fire Code

Test BFD IX-1

California T.B. 117 - 2013

FMVSS 302

Federal Aviation Specification

FAR 25.853(a) Appendix F, Part 1 (a)(1)(ii)

Federal ST. 191A M 5903.1

IMO FTP 2010 Code

MSC.307(88) Part 8, 3.1 & 3.2

NFPA 260 - Class I

Port Authorities of NY & NJ

UFAC - Class I

\*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Our vinyls, when tested with suitable component materials, may comply with California Technical Bulletin 133 and Boston Fire Code - Test BFD IX-1.

All Spradling International's vinyl- and PU-coated fabrics contain flame retardant additives.

## Specifics

Weight: 30 oz.

Width: 54 in.

Roll Size: 30 yd.

## Applications

Corporate

- Office
- Education

Healthcare

Hospitality

- Hotel | Motel | Casino
- Restaurant
- Theaters | Convention Centers